HR8038 12V K2

DC AXIAL FAN | TECHNICAL DATASHEET

80x80x38 mm | 12 VDC | K2



Frame Type: Black PBT (UL94V-0)
Impeller: Black PBT (UL94V-0)
Bearing: Two Ball & (Sleeve or Hydraulic Bearing)
Operation Temperature: -10°C~70°C (Ordinary humidity)
Storage Temperature: -40°C~80°C (Ordinary humidity)
Lead wire: (+) Red,(-) Black,(FG/RD)Yellow,(PWM) Blue
Safety: CE approved, RoHS
Ingress of Protection: IP42 or IP55
Unit Weight:180g
Level of error:±10%

ELECTRICAL & PERFORMANCE SPECIFICATIONS


Model	Rated VDC	Operating VDC	Current A	Power W	Speed RPM	Air flow CFM	Air flow m³/min	Pressure mmH2O	Pressure Pa	Noise dBA
HR8038HD1	12	7~15	3.20	38.40	13000	112.19	3.18	65.14	638.81	70.90
HR8038MD1	12	7~15	1.40	16.80	10000	82.68	2.34	45.29	444.14	63.90
HR8038LD1	12	7~15	0.75	9.00	8000	65.67	1.86	31.38	307.73	56.20

AVAILABLE FUNCTIONS


RP	AS	CS	CL	OV	SS	FG	RD/RD/b	LD	PPWM	VPWM	TC	RC
Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			

Function availability depends on the ordered configuration. Confirm wiring and pinout before use.

PERFORMANCE CURVES



DIMENSIONS (mm)



Specifications are subject to change. Contact HERAYS for configuration requirements.